# **GOT-812**

# 12.1" SVGA/XGA TFT IP66-rating Fanless Touch Panel Computer (-20°C ~ +55°C)












■ 12.1" SVGA/XGA high brightness color TFT LCD

- IP66-rating whole system water/dust-proof design
- Fanless system with Intel® Atom™ processor N270
- Wide operating temperature range of -20°C ~ +55°C
- Sunlight readable design: low-reflective T/S
- Suspension and VESA mounting

**Features** 



### Introduction

The GOT-812 is specially designed for heavy-duty & outdoor applications. Its IP66-rating stainless steel housing protects entire system from outside damage of water, powder and dust. It also outfits sunlight readable technology and wide operating temperature range of  $^{-20\,^{\circ}\text{C}}$  c  $^{+}55\,^{\circ}\text{C}$ . Thus, this robust unit is best suited for outdoor environments in extreme sunny or rainy day, dusty or wet spaces in food factories or kitchens and more harsh applications, such as steel factories, transformer stations and vessels.

#### IP66-sealed system

The GOT-812 adopts a water/dust-proof housing design and six IP66-rating connectors. It passes entire system IP66 test by SGS and verified salt mist test and marine grade by IEC60945.

#### Sunlight readable design

Its sunlight readable technology with LED tech high brightness 1000 nits color display and low reflective touchscreen allows the screen legible even under strong sunlight

#### Wide temp. (-20°C ~ +55°C) & anti-vibration (2G) design

The GOT-812 supports wide temperature of -20°C ~ +55°C. Besides, the patent of anti-vibration for SSD ensures system reliability and stability.

## **Specifications**

Front Bezel	Stainless type 316		BIOS	AMI with Axiomtek standard	
LCD Panel	Display Type	12.1" SVGA TFT LCD (GOT-812L) 12.1" XGA TFT LCD (GOT-812LR)		features; such as, SmartView Ethernet Boot ROM	
	Brightness (cd/m²)	1000 nits (GOT-812LR) 450 nits (GOT-812L)		(RPL & PXE), customer CMOS backup	
	Resolution	800 x 600 (GOT-812L) 1024 x 768 (GOT-812LR)	Storage	1 x 2.5" SSD 1 x CompactFlash™	
	Viewing Angle (H/V)	100°/120° (GOT-812L) 160°/140° (GOT-812LR)	Watchdog Timer Onboard	255 levels, 1~255 sec. Integrated in Intel® 945GSE	
Main System	CPU	Intel® Atom™ processor N270 1.6 GHz	Graphics	meeg. acea in inter 7 is est	
	Chipset	Intel® 945GSE+ICH7M		i	
	System Memory	1 x 200-pin DDR2 SODIMM max. up to 2 GB			

I/O Connector	2 x RS-232 (COM 1/2)
	2 x USB 2.0
	1 x 10/100/1000Mbps Ethernet
Expansion Interface	PCIe Mini card
Touch screen	5-wire resistive low reflective type (GOT-812LR)
	5-wire resistive type (GOT-812L)
Power Supply	Power input 12Vpc/24Vpc
Dimensions	304mm (11.97") (W) x 58.5mm (2.3") (D) x
	248mm (9.76") (H)
Weight (net/gross)	4.5 kg (9.92 lb)/6 kg (13.23 lb)
Environmental	Operation temperature: -20°C ~ +55°C
	Relative humidity: 10% ~ 95% @ 40°C, non-condensing
	Operation vibration:
	2G, 5 ~ 500Hz, random for 2.5" SSD
	3G, 5 ~ 500Hz, random for CompactFlash™
Certification	CE/IEC60945/DNV 2.4 (compliant)

<sup>\*</sup> W.T.: Wide Temperature. All W.T. supported products have to be sorted by Axiomtek.

# **Ordering Information**

Sunlight readable ty	/pe		
GOT-812LR	12.1" IP66-rating sunlight readable touch panel		
(P/N: E22B812102)	computer (1000 nits) w/ Intel® Atom™ processor N270		
GOT-812LR-WiFi 12.1" IP66-rating WiFi sunlight readable touch pa			
(P/N: E22B812103)	computer (1000 nits) w/ Intel® Atom™ processor N270		
Normal type			
GOT-812L	12.1" IP66-rating heavy-duty touch panel computer		
(P/N: E22B812100)	w/ Intel® Atom™ processor N270		
GOT-812L-WiFi	12.1" IP66-rating WiFi heavy-duty touch panel		
(P/N: E22B812101)	computer w/ Intel® Atom™ processor N270		

## **Optional Accessories**

822B8120070E	Keyboard kit
OZZDO IZOUTOZ	
822B8120080E	Suspension kit
594B8122100E	Water proof COM port cable
594B8122820E	Water proof USB cable
594B8122720E	Water proof LAN cable
394D01ZZ/ZUE	Water proof LAN cable
50964116000E	60W/12V power adapter w/ M12 connector
J0704110000L	ouw/12v power adapter w/ M12 connector
VFSA ARM	
V L JA AIWI	

# **Optional EOS Installation**

Windo	w <sup>®</sup> XP Embedde	ed		
Windo	w <sup>®</sup> CE.NET			
Linux				

## **Optional OS Installation**

Windows® XP

Touch Panel
Computers for
Various Industry

Digital Signage and Display

Medical Panel

Medical Grade Monitors

GOT Fanless Touch Panel Computers

Touch Panel Computers for Infotainment

Touch Panel Computers for Automation

Touch Panel Monitors for Automation

Open Frame Panel Computers

## **Dimensions**

