

Getac

Rugged Mobile Computing Solutions

PS336

Fully Rugged Handheld



- 600 nits 3.5" VGA Sunlight Readable TFT LCD with Blanview Technology
- Optional 3.5G WWAN (HSPA+/UMTS /EDGE/GPRS/GSM)
- SiRFstarIV™ High Sensitivity GPS
- Optional FlexiConn™ 3-in-1 Card Reader/1D Barcode Reader/Long Range Bluetooth/13.56MHz RFID Reader



1D Laser
Barcode Reader



RFID Reader or
Long Range BT



3-in-1
Card Reader



Office Dock





Specifications

Operating System	Windows® Embedded Handheld 6.5 Professional Windows® Embedded Handheld 6.5 Classic
Mobile Computing Platform	TI AM3715 1GHz
Display	3.5" TFT LCD VGA (480 x 640) 600 nits Blanview transmissive display Pressure sensitive touchscreen
Storage & Memory	512MB MDDR 256MB NAND flash and 8GB iNAND
Keypad	Phone numeric keypad
Expansion Slot	FlexiConn™ Micro SDHC (up to 32GB)
I/O Interface	Serial port (9-pin; D-sub) x 1 USB OTG (client 2.0 and host 2.0; 5-pin; type Mini AB) x 1 Microphone x 1 Speaker x 1 DC in Jack x 1 Docking connector (4-pin) x 1
Communication Interface	Optional 3.5G WWAN (HSPA+/UMTS/EDGE/GPRS/GSM) 802.11 b/g/n Bluetooth (v2.1+EDR class 2) GPS (with internal antenna)
Software	Microsoft Internet Explorer Mobile® Windows® Office Mobile 2010 Windows® Office Outlook Mobile Windows® Media Player Mobile Microsoft ActiveSync 4.5 for data sync Getac Camera geo-tagging software
Power	AC charger (24W; 12V/2A, 100-240VAC; 50 / 60 Hz) Li-Ion smart battery (5600mAh) (up to 12 hours of battery life) ⁱ Charging time: Sleep mode, approx. 3.5 Hrs. LifeSupport™ battery swappable technology ⁱⁱ
Dimension (W x D x H) & Weight	8.9 x 3 x 17.8 cm (3.5" x 1.18" x 7.01"), 530 g (18.69 oz) without 3G module ⁱⁱⁱ
Field Service Feature	GPS: SiRFstarIV™ 5M pixels auto focus camera with LED light E-compass Altimeter Optional 13.56MHz RFID and contactless smart card reader (ISO 15693 and 14443 A/B compliant)

GPS Sensor Specification	Chipset: SiRFstarIV™ Receiver Type: L1 (C / A) Channels: 48 channels all-in-view tracking Update Rate: 1 Hz Horizontal Accuracy: i) Autonomous: 2.5 m / 8.2 ft ii) DGPS ^{iv} : 2.0 m / 6.56 ft Cold Start Time: 35 sec average Hot Start Time: 1 sec average Reacquisition: 0.1 sec average
Rugged Feature	MIL-STD-810G and IP68 certified Vibration resistant Drop resistant (26 drops from 1.82m / 6ft) Tumbling resistant (1,000 cycles; 0.5 m / 1.6 ft)
Environmental Specification	Temperature: - Operating: -30°C to 60°C / -22°F to 140°F - Storage: -40°C to 70°C / -40°F to 158°F Humidity: - 95% RH , non-condensing
Alphanumeric Data Entry	Soft input panel (SIP) on screen keyboard Transcriber handwriting recognition Phone numeric keypad Nuance XT9® Soft input panel (SIP) ^v
Security Feature	WiFi for WPA / WPA2 operation Authentication: OPEN, SHARED-KEY, PEAP (MS-CHAPv2, GTC, MD5), EAP-TLS, EAP-FAST, EAP-TTLS (PAP, CHAP, MS-CHAP, MS-CHAPv2, PAP/Token Card, EAP with GTC) Encryption: WEP, AES, TKIP
Regulation	CE, FCC, UL, BSMI, NCC, JRF, VCCI, PSE, A-Tick / C-Tick
Inbox Accessories	- AC charger - USB cable - Hand strap - Quick start guide - Battery - Stylus - Stylus tether
Optional Accessories	- Office dock - Vehicle charger - Battery charger - Carry bag - Hand strap with belt clip - I/O dust cover - USB host cable - USB to RS232 converter cable - Vehicle mount ^{vi} - FlexiConn™ 3-in-1 card reader - FlexiConn™ 1D barcode reader - FlexiConn™ long range bluetooth - FlexiConn™ 13.56MHz RFID and contactless smart card reader

PS336 Configuration

	Specification				
	WWAN	Memory Storage	Altimeter	Embedded	
	HSPA+	1GB	ICM	E-Compass	HF RFID
PS336 Basic		●	●	●	
PS336 Basic RF		●	●	●	●
PS336 Premium	●	●	●	●	
PS336 Premium RF	●	●	●	●	●

ⁱ Battery performance will vary with software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. Battery life and charge cycles vary by use and settings.
ⁱⁱ The system will stay operating (within 120 seconds in standby mode) when user swaps the battery.
ⁱⁱⁱ Weight varies from configurations and optional accessories.
^{iv} Supported SBAS: WASS, EGNOS, MSAS, GAGAN.
^v Japanese OS image is excluded.
^{vi} Supported by third party supplier. For more details, please contact Getac sales team.



Getac Technology Corporation

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist.,
 Taipei City, 11568, Taiwan, R.O.C.
 Tel: +886 2 2785 7888
 globalmarketing@getac.com
 www.getac.com

